NEW BUNCH COMPRESSION MONITOR(S)

Bernhard Schmidt -FLA-13.3.2007 - FLASH SEMINAR-

WHY THIS?

- existing BCM measure INTEGRAL intensity above ~80 μm wavelength (quartz window)
- the lasing peak radiates at much shorter wavelengths, even with 3rd harmonic
- get more information on bunch shape by looking at spectral structure

WHY THIS?







• use diamond window to extend spectrum

- use diamond window to extend spectrum
- do NOT use diffraction radiators

- use diamond window to extend spectrum
- do NOT use diffraction radiators
- spectral information instead of integral

- use diamond window to extend spectrum
- do NOT use diffraction radiators
- spectral information instead of integral
 - filter(s)

- use diamond window to extend spectrum
- do NOT use diffraction radiators
- spectral information instead of integral
 - filter(s)
 - single stage spectrometer

- use diamond window to extend spectrum
- do NOT use diffraction radiators
- spectral information instead of integral
 - filter(s)
 - single stage spectrometer
 - multi-stage spectrometers



NEXT STEPS

- continue developments at THz beam-line
- set up compact, monolithic four stage spectrometer
- install diamond window exit port for CSR at BC3
- install spectrometer for permanent use at this port
- install another device at dog-leg









technicalities



technicalities



STATUS & PLANS

- vacuum parts ordered, installation end of April
 - diamond window(s) ordered
 - mirror mechanics ordered
- start with restricted version detector (few channels)
- have compact broad band spectrometer (CBS) ready by end of the year